





MARKING:

THE MARKING OF THE CORDS:

◁VDE▷ H05VV-F 3×1.0mm² Ningbo Jiangfeng Plastic & Chemistry Co.,Ltd

THE MARKING OF THE PLUG:

B-03 16A 250V~    (D) (F1)
 (N) (S) (OVE) (NF) 

THE MARKING OF THE CONNECTOR:

B-04 10A 250V    (D) (F1) (N) (S)

PART NO	LENGTH	COLOR
504226	3000±60mm	BLACK
504227	5000±100mm	BLACK
504229	10000±200mm	BLACK
504339	3000±60mm	RED
504340	5000±100mm	RED
504342	3000±60mm	GREEN
504343	5000±100mm	GREEN
504345	3000±60mm	YELLOW
504346	5000±100mm	YELLOW
504348	3000±60mm	BLUE
504349	5000±100mm	BLUE
504353	3000±60mm	ORANGE
504354	5000±100mm	ORANGE

DIMENSIONS AND CHARACTERISTICS OF 1.0mm² CORD
 RATED VOLTAGE 300/500V
 NUMBER OF CORE 3
 CONSTRUCTION 32/0.2

3	1	B-04 IEC60320-C13			
2	1	Cable VDE H05VV-F 3×1.0mm ²			
1	1	B-03 (CEE7/7)			
Itemref	Quantity	Title/Name, designation, material, dimension etc			Article No./Reference
Designed by	Checked by	APPROVED_BY_DATE	File name	Date	Scale
DESIGNED_BY	CHECKED_BY		FILENAME	2022.10.16	SCALE
504227			CAFCA DIGICABLE		
			Edition	Sheet	
			EDITION	SHEET	