






**MARKING:**

**THE MARKING OF THE CORDS:**

◁VDE▷ H05VV-F 3×0.75mm<sup>2</sup> Ningbo Jiangfeng Plastic & Chemistry Co.,Ltd

**THE MARKING OF THE PLUG:**

B-03 16A 250V~    (D) (F1)

(N) (S)  (NF) 

**THE MARKING OF THE CONNECTOR:**

B-04 10A 250V    (D) (F1) (N) (S)

PART NO	LENGTH	COLOR
504213	600±15mm	BLACK
504218	1800±30mm	BLACK
504219	1800±30mm	GREY
504338	1800±30mm	RED
504341	1800±30mm	GREEN
504344	1800±30mm	YELLOW
504347	1800±30mm	BLUE
504352	1800±30mm	ORANGE

DIMENSIONS AND CHARACTERISTICS OF 0.75mm<sup>2</sup> CORD  
 RATED VOLTAGE 300/500V  
 NUMBER OF CORE 3  
 CONSTRUCTION 42/0.15

3	1	B-04 IEC60320-C13			
2	1	Cable VDE H05VV-F 3×0.75mm <sup>2</sup>			
1	1	B-03 (CEE7/7)			
Itemref	Quantity	Title/Name, designation, material, dimension etc			Article No./Reference
Designed by	Checked by	APPROVED_BY_DATE	File name	Date	Scale
DESIGNED_BY	CHECKED_BY		FILENAME	2022.10.10	SCALE
504338			CAFCA DIGICABLE		
			EDITION	SHEET	