



P1: M-Y536A  
M-536A  
P2: M-780A



\*NOTE: All relevant materials are complied with RoHS directive .

6	BLACK HEAT SHRINK TUBE $\phi$ 1.0*3mm	A4HA23-0959	1	M959
	BLACK HEAT SHRINK TUBE $\phi$ 3.0*9mm	A4HA10-0959	2	M959
	MOLDED PVC BLACK	H1BF01-0304K09		M304
5	BLACK HEAT SHRINK TUBE $\phi$ 1.0*10mm	A4HA23-0959	1	M959
	BLACK HEAT SHRINK TUBE $\phi$ 3.0*9mm	A4HA10-0959	2	M959
	HEX-NUT 5*4.0mm, #4-40	A6BC01-0095	2	M95
	MOLDED PE COLOR TRANSPARENT	A5BA02-0280		M280
4	MOLDED PVC BLACK	H1BF01-0304K09		M304
	USB 3.0 CABLE, 28AWG*1PAIR+(28AWG*1PAIR+D+F-AL)*2PCS+24AWG*2C+AMA BRAID(65%), OD 5.8mm JACKET BLACK, DRAWING NO. EUAB2801P2802P2402C-371	H5KS04-0304K09	Xmm	M304
	SCREW 5.2*14mm, 4-40#	A6AC12-0095	2	M95
2	USB A MALE 3.0, GOLD FLASH ON CONTACTS BLUE INSULATOR, SOLDER THREE PIECES TYPE	A1HA48-0454	1SET	M454
1	USB A FEMALE 3.0, GOLD FLASH ON CONTACTS, BLUE INSULATION	A1HC19-0454	1	M454
DESCRIPTION			QTY	Supplier



PART NO. 9J50-4		Revision:		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm
APPROVED				
CHECKED	HU			
DRAWING	JIANG			
DATE	15/DEC/18	ITEM NO.	153082	UNIT:mm

REV.4 2018.12.15	MODI FYPLUG SUPPLIER	CHECKED
REV.3 2015.11.20	MODIFY CONN SUPPLIER FOR M656 TO M846 AND MODIFY I TM NO.	
REV.2 2014.12.09	MODI FYCONN SUPPLIER FOR M108 TO M656 AND M432	
REV.1 2014.04.21	MODI FY 480mm "QTY"	